JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

TO-3P Plastic-Encapsulate Transistors

2SD718 TRANSISTOR (NPN)



FEATURES

- High Breakdown Voltage
- Complementary to 2SB688

APPLICATIONS

- Power Amplifier Applications

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	120	V
V_{CEO}	Collector-Emitter Voltage	120	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current	8	A
P_C	Collector Power Dissipation	3	W
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	42	℃/W
T_J,T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	℃

ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=100μA,I_E=0	120			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=50mA,I_B=0	120			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=100μA,I_C=0	5			V
Collector cut-off current	I_{CBO}	V_{CB}=120V,I_E=0			10	μA
Emitter cut-off current	I_{EBO}	V_{EB}=5V,I_C=0			10	μA
DC current gain	h_{FE}*	V_{CE}=5V, I_C=1A	55		160	
Collector-emitter saturation voltage	$V_{CE(sat)}$*	I_C=5A,I_B=500mA			2.5	V
Base-emitter voltage	V_{BE}*	V_{CE}=5V, I_C=5A			1.5	V
Collector output capacitance	C_{ob}	V_{CB}=10V,I_E=0, f=1MHz		280		pF
Transition frequency	f_T	V_{CE}=5V,I_C=1A, f=1MHz		10		MHz

*Pulse test

CLASSIFICATION OF h_{FE}

RANK	R	O
RANGE	55-110	80-160

TO-3P Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.600	5.000	0.181	0.197
A1	1.200	1.600	0.047	0.063
b	0.800	1.200	0.031	0.047
b1	2.800	3.200	0.110	0.126
b2	1.800	2.200	0.071	0.087
c	0.500	0.700	0.020	0.028
c1	1.450	1.650	0.057	0.065
D	15.450	15.850	0.608	0.624
E	13.700	14.100	0.539	0.555
E1	3.200 REF		0.126 REF	
E2	3.300 REF		0.130 REF	
E3	13.450 REF		0.530 REF	
F1	13.400	13.800	0.528	0.543
F2	9.400	9.800	0.370	0.386
L	39.900	40.300	1.571	1.587
L1	23.200	23.600	0.913	0.929
L2	20.300	20.600	0.799	0.811
Φ	6.900	7.100	0.272	0.280
G	5.150	5.550	0.203	0.219
e	5.450 TYP		0.215 TYP	
H	5.000 REF		0.197 REF	
h	0.000	0.300	0.000	0.012