JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

SOD-323 Plastic-Encapsulate Diodes

B5817WS-5819WS SCHOTTKY BARRIER DIODE



FEATURES

For use in low voltage, high frequency inverters
Free wheeling, and polarity protection applications

MARKING:

B5817WS:SJ	B5818WS:SK	B5819WS:SL
		

The marking bar indicates the cathode
Solid dot = Green molding compound device,if none, the normal device.

Maximum Ratings and Electrical Characteristics, Single Diode @Ta=25℃

Parameter	Symbol	B5817WS	B5818WS	B5819WS	Unit
Non-repetitive peak reverse voltage	V_{RM}	20	30	40	V
Peak repetitive peak reverse voltage Working peak reverse voltage DC blocking voltage	V_{RRM} V_{RWM} V_R	20	30	40	V
RMS reverse voltage	$V_{R(RMS)}$	14	21	28	V
Average rectified output current	I_O	1			A
Non-repetitive Peak Forward Surge Current @t=8.3ms	I_{FSM}	9			A
Repetitive peak forward current	I_{FRM}	1.5			A
Power dissipation	Pd	250			mW
Thermal resistance junction to ambient	$R_{\theta JA}$	400			℃/W
Junction temperature	T_J	125			℃
Storage temperature	T_{STG}	-55~+150			℃

ELECTRICAL CHARACTERISTICS (Ta=25℃ unles s other wise specified)

Pa rameter	Symbol	Test c onditions	Min	Max	Unit
Reverse breakdown voltage	$V_{(BR)}$	I_R= 1mA B5817WS B5818WS B5819WS	 20 30 40		V
Reverse voltage leakage current	I_R	V_R=20V B5817WS V_R=30V B5818WS V_R=40V B5819WS		1	mA
Forward voltage	V_F	B5817WS I_F=1A I_F=3A		0.45 0.75	V
		B5818WS I_F=1A I_F=3A		0.55 0.875	V
		B5819WS I_F=1A I_F=3A		0.6 0.9	V
Diode capacitance	C_D	V_R=4V, f=1MHz		120	pF

Forward Characteristics



Reverse Characteristics



Capacitance Characteristics



Power Derating Curve



SOD-323 Package Outline Dimensions







Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A		1.000		0.039
A1	0.000	0.100	0.000	0.004
A2	0.800	0.900	0.031	0.035
b	0.250	0.350	0.010	0.014
c	0.080	0.150	0.003	0.006
D	1.200	1.400	0.047	0.055
E	1.600	1.800	0.063	0.071
E1	2.550	2.750	0.100	0.108
L	0.475 REF.		0.019 REF.	
L1	0.250	0.400	0.010	0.016
θ	0°	8°	0°	8°

SOD-323 Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE
JSCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOD-323 Tape and Reel

SOD-323 Embossed Carrier Tape



Packaging Description:

SOD-323 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOD-323	1.48	3.3	1.25	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOD-323 Tape Leader and Trailer



SOD-323 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	